

# GSSI GROUP

## LED GREENLIGHTING

Save Energy . . . Save Money . . . Save the Earth

### T8K - Tube Lights



### Specifications and Characteristics

Lighting	T8K-2-96	T8K-2-120	T8K-4-192	T8K-4-240	T8K-4-360	T8K-6-288	T8K-8-344
Luminaire:	96 LEDs	120 LEDs	192 LEDs	240 LEDs	360 LEDs	288 LEDs	344 LEDs
Rated Lumens:	675	800	1,350	1,650	1,950	2,050	2,700
Efficacy lm/W	68	80	75	83	78	64	75
Correlated Color Temperature (CCT):	CW - 5,000 ~ 6,000 K						
	PW - 4,000 ~ 4,500 K						
	WW - 3,000 ~ 3,500 K						
Color Rendering Index (CRI)	Ra > 80						
Photometry:	Type C						
Warranty:	5 Years, 50,000 hrs.						
<b>Electrical</b>							
Total Watts:	10W	10W	18W	20W	25W	32W	36W
Rated Voltage:	120~277V						
IP Rating:	IP 65						
Certification:	UL, TUV, GS, CE, RoHS						
Power Factor	0.915						
<b>Environmental</b>							
Temperature Range Ambient:	-30°C ~ 50°C						
Humidity Range	10% ~ 90% relative humidity						
<b>Packing Information</b>							
Dimension:	T8x24"		T8x48"		T8x72"	T8x96"	
Pieces per carton:	30						