

GSSI GROUP

LED GREENLIGHTING

Save Energy . . . Save Money . . . Save the Earth

YC LED 'Corn Light' CFL Replacement Bulbs

(suitable for use in six or eight-inch diameter aluminum cylinder surface, pendant or trunion mounts.)



Specifications and Characteristics

Lighting	4 watt	5 watt	6 watt	7 watt	8 watt	9 watt
Luminaire:	64 LEDs	84 LEDs	108 LEDs	124 LEDs	144 LEDs	156 LEDs
Rated Lumens:	350	460	595	680	790	860
Efficacy lm/W	88	92	99	97	99	96
Correlated Color Temperature (CCT)	CW - 5,000 ~ 7,000 K					
	PW - 4,000 ~ 4,500 K					
	WW - 2,700 ~ 3,500 K					
Color Rendering Index (CRI)	Ra > 80					
Photometry:	Type C					
Warranty:	5 Years, 50,000 hrs.					
Electrical						
Total Watts:	4W	5W	6W	7W	8W	9W
Rated Voltage:	120 ~ 220V					
IP Rating:	IP 65					
Certification:	UL, TUV, GS, CE, RoHS					
Available Base (screw-in)	E12, E14, E26, E27					
Available Base (plug-in)	G23-2, GX23-2. G24D. G24Q					
Environmental						
Temperature Range Ambient:	-30°C ~ 50°C					
Humidity Range	10% ~ 90% relative humidity					
Miscellaneous						
Equivalent (W) Replacement	10W CFL	13W CFL	26W CFL*	26W CFL*	26W CFL*	26W CFL*
Pieces per carton:	50					

* 26W is currently the highest power CFL available.